< INTELLOF		: GIA-RDP82-00457	R008700410002- X1	9)(1)		
د. مسي بي. د	CLASSIFICATION SAND			454		
	CENTRAL INTELLIGENCE	URITY INFORMATION AGENCY	REPORT NO.	<u>'</u>		
	INFORMATION	REPORT	CD NO.	25X1A		
COUNTRY	Germany (Russian Zone)		DATE DISTR.	14 December 1951		
SUBJECT	Radio Services of the Ministerium fur Post-und Fernmellewesen		NO. OF PAGES NO. OF ENCLS.	3		
PLACE ACQUIRED	DO NOT	CIRCULATE	(LISTED BELOW)			
DATE OF INFO.	25X1A	25X1X	SUPPLEMENT TO REPORT NO.	0		
OF THE UNIVERSED OF ITS CONTENT	T CONTAINS INPOSSATION AFFECTING THE RATIONAL DEFENSE OTATES WITHIN THE DEFENSE OF THE REPIONAGE RACE UP DEC. AS ACCUMENT. ITS TRANSMISSION ON THE REVELATION DEC. AND ALBERT TO AN UNLAUFRONIZED PRESON 12 PRO- W. REPRODUCTION OF THIS FORM IS PROBUBITED.	Document No. 2 No Change in Clas	LUATED INFORMA	ATION		
SOURCE		Declassified Class. Changed To	: TS S (C)			
I. R	roadcasting	3m.h.: KR 70-2 Dale: 2 1 AUG 1	978_	25X1		
	Inder the direction of the Ministerium fuer Post - und Fernmeldewesen (Fost and Telegraph Ministry (MFF) the construction of the following transmitters in early 1951 was planned in Nauen: a. A twin transmitter to be used as spare transmitter for Berlin. This installation is designed for two transmitters, each having an output of 150 kw. The transmitters will operate either on the same or on two different antennas. The order for the construction of this installation was placed with the R-F-T Funkwerk (Radio- und Fernmeldetechnik) Köpenick, represented by Promiser. Completion is scheduled for 1952. The transmitting tubes were ordered at the Oberspreawerk. A one-kw transmitter was tosted at various points in the vicinity of Berlin, such as Nauen, Koenigswusterhausen, Wuhlheide, Rangsdorf and Treptow and field strength measurements were taken in an attempt to determine the most favorable location for the twin transmitter. b. A 50-kw single side band transmitter for connercial radio traffic to East Asia. c. A 50-kw short-wave broadcast transmitter. Proposals for the eraction of additional transmitters in Nauen were not approved for 1951/1952.					
	All matters dealing with the erection of the twin transmitter are controlled by Department M of the Post - und FernmeldetechnischesZentralamt (Central Office for Postal and Telecommunications Techniques) (PFZ). By early 1951, the definite location of the transmitter had not been announced by the PFZ; its possible location at either Hauen or Uhlenhorst near Koepenick was only mentioned unofficially. The power house of the planned instal ation is scheduled to be provided with five type 8V=55 Diesel engines manufactured by the Goerlitzer Maschinenbau. The required buildings are to be built by the Bau Whion Berlin and to be completed by 1 august 1951.					
3.	About the beginning of 1951, the broadcasting station in Schwerin was so re-equipped and reorganized that it was able to operate on any frequency of the medium wave band (500 to 1,600 km;) on 30 minutes notice. In late April, trial transmissions were made on a frequency of 728 kms. The Erfurt, Potsdam and Bernburg broadcasting stations are					
	CLASCIFICATION: STEPHEN	IAL				
Corter	CLASSIFICATION CHARLES			25X1		
ARMY I	X NAVY X NSRB OSI EV X STRIBLE OSI EV X	O I I O IV				

scheduled to be reorganized along the same lines in 1951.

II. Commercial Radio Services.

- 4. In March 1951 it was learned that the frequency telepraphic equipment required for the Ferlin-Moscor convercial radio link and ordered from the **Smahsenwerk Radeberg would**not be **delivered** in the near future, Radio connection between Moscow and Berlin is, therefore, maintained by worse telegraphy on a frequency of 10,210 kc, with the call sign DNG 2 for communications from Rerlin to Moscow, and a frequency of 11,020 kc and the call sign RBK for traffic from Moscow to Berlin. Operating times for this radio link are from 9 and 11 a.m. as long as required for the handling of radio traffic, and from 1 p.m. to midnight.
- German radio traffic between Berlin and Peiping is hampered by the fact that transmitting facilities are used for boviet radio services during the most favorable transmitting times. In December 1950, it was requested that, in addition to previously used frequencies, which proved unsatisfactory during the winter months, i.e. frequencies of 7,917.5, 10,440 and 17,520 kc, the use of the following frequencies and call signals be approved: 4,620 kc, DKS; 4,010 kc, DKT; 3,395 kc, DKU; 3,160 kc, DKV. Only in mid-February 1951 did the Russians approve trial transmissions on these frequencies. The following frequencies and call signals are in use for traffic from Peiping to Berlin: 7,496 kc, BAZ 2; 13,118 kc, BAX 2; 15,820 kc, BAP 2; 18,160 kc, BAX.
- The equipment required for the diplomatic radio service of the Russian Zone of Germany, i.e. the KN-2 program, will be manufactured and installed by the Punkwerk Koepenick. In late March 1951, this radio net, except for trial transmissions between Berlin and Prague, was not yet in operation. In early February 1951, it was learned that the personnel scheduled to operate the diplomatic radio service had been trained at the Central Telegraph Office in erlin after careful political screening. Since the 800-kw transmitter scheduled to be erected in Berlin had not yet been delivered, the Russian Zone Postal Administration intended to set up a 1.2-kw transmitter in Coenigswusterhausen by 31 March 1951. This transmitter had previously been at the disposal of the Funkwerk in Erfurt for the testing of transmitting tubes.

III. Ultra-Short Wave Radio Operations.

7. In April 1951, the use of the following frequencies was requested from the Russian Lone Postal Administration for the 100-Watt television transmitter set up in the Oberspreawerk:

Video transmitter: 96.75 to 105 megacycles;

Audio transmitter: 105.5 megacycles = 75 kc.

Link between the television studio in Adlershof and Oberschoeneweide: 1,500; 3,000; 5,000 and 10,000 megacycles.

IV. Ionospheric and Troposphoric Research Works

8. In February 125, the Heinrich Hertz Institute requested the Russian Zone Postal Administration for permission to operate on the following

a. For impulse senders used for the exploration of the ionosphere; 4,062 kc for one 1-kw transmitter; 1 to 20 megacycles for a 1-kw wide band ionosphere sounding transmitter. Impulse frequency: 50 copeso, impulse period: 50 to 100 microseconds.

IZA	AL	
CONFIDENT		
$CO_{I,I}$.		

25X1

b. For a 50-Watt transmitter used in connection with research work on propagation of waves in the troposphere, which previously had operated on frequencies of 40 to 42 megacycles, frequencies of 68; 71; 76; 85; 81; 98; 85; 105; 145; 174; 200 and 236 megacycles. To date the SCC has refused to approve the use of these frequencies.

CONFILENTIAL

25X1

25X1